



BHARAT SPRING LOADED CULTIVATOR Code **BEBSLC**



Reversible
Shovels

Heavy Duty
3-Point
Linkage

Heavy Duty
Springs

Forged Tyne



Features & Benefits

- **BHARAT spring loaded Cultivator/tiller is simple in design but sturdy in performance.**
- It is suitable for use in soft and medium soil conditions.
- Loosens and aerates the soil to a depth of upto nine inches.
- When one tine strikes a buried object, the others continue to work at correct depth.
- The Dual spring loaded tyne assemblies derive their strength from heavy duty angles, which once fixed to the main frame cannot move out of position.
- It prepares seed beds quickly and economically.
- Comes with high quality reversible steel shovels & high Quality spring steel springs.

Product Specifications

| Description | BEBSLC-7 | BEBSLC-9 | BEBSLC-11 | BEBSLC-13 | BEBSLC-15 |
|----------------------|---|----------|-----------|---------------------------------|-----------|
| Frame (mm) | 75x40 Channel & 50x8 Pair Flat | | | 100x50 Channel & 50x8 Pair Flat | |
| Tynes (mm) | 50x22 Forged | | | | |
| No. of Tynes | 7 | 9 | 11 | 13 | 15 |
| Type of Disc / Blade | Reversible Shoe Type & 8mm High Carbon Steel | | | | |
| Tyne Spacing (mm) | 228(9") | | | | |
| Expansion Springs | O.D. 50, Wire Dia. 9.5 (25 Coil) (Spring Steel) | | | | |
| Length (mm) | 1542 | 2000 | 2458 | 2916 | 3374 |
| Width (mm) | 840 | | | | |
| Height (mm) | 1040 | | | | |
| Width of Cut (mm) | 1468 | 1925 | 2382 | 2839 | 3296 |
| Weight (Kg. Approx) | 170 | 210 | 270 | 330 | 425 |
| Tractor Power (HP) | 30~35 | 40~45 | 50~55 | 60~65 | 70~75 |

*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification / improvement.