





- UNIVERSAL Extra heavy duty spring loaded Cultivator/tiller is designed for toughest tillage operations.
- It is suitable for use in stone and root obstructed soil.
- Loosens and aerates the soil to a depth of upto nine inches.
- When one tyne strikes a buried object, the others continue to work at correct depth
- Spring Loaded Tyne Assemblies derive their strength from heavy duty angles, which once fixed to the immensely strong main frame cannot move out of position.
- It prepares seed beds quickly and economically.
- Comes with high quality reversible steel shovels & high quality spring steel springs.

## **Product Specifications**

**GROW WITH US** 

Description	BEEHDSLC-5	BEEHDSLC-7	BEEHDSLC-9	BEEHDSLC-11	BEEHDSLC-13	BEEHDSLC-15
Frame (mm)	100x50 Channel & 65x6 Angle Pair					
Tynes (mm)	50x25 Forged					
No. of Tynes	5	7	9	11	13	15
Type of Disc / Blade	Reversible Shoe Type & 8mm High Carbon Steel					
Tyne Spacing (mm)	228(9")					
Expansion Springs	O.D. 50, Wire Dia. 10 (28 Coil) (Spring Steel)					
Length (mm)	1084	1542	2000	2458	2916	3374
Width (mm)	880					
Height (mm)	1185					
Width of Cut (mm)	1010	1468	1925	2382	2839	3296
Weight (Kg. Approx)	210	225	285	345	410	480
Tractor Power (HP)	20~25	30~35	40~45	50~55	60~65	70~75

\*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification / improvement.