

STANDARD DISC PLOUGH Code BESMDP

Heavy Duty
Spindle Assy.



Heavy Duty
Colter
with Shocker



Adjustable Disc
spacing



Moveable Weight
for Improved
Penetration



Features & Benefits

- Standard Disc Ploughs are well designed to work in all types of soils & can be use easily in hard soils & in rocky & rooted areas.
- Standard Disc Ploughs can handle the toughest ploughing jobs with ease.
- Compatible with a variety of tractors (45 to 75 HP).
- An adjustable and spring-loaded furrow wheel/coulter disc takes care of the side draft and makes sure that the implements moves smoothly.
- Coulter Disc & Shocker assembly keeps the Plough perfectly aligned.
- Horizontally adjustable disc spacing.
- Highly adjustable disc hubs to change disc penetration & disc position angle.
- Available with the option of high quality Universal Boron steel & high carbon steel discs.
- Available in 2 & 3 bottom configurations.
- Moveable extra weight for improved penetration & stability.

Product Specifications

Description	BESMDP-2	BESMDP-3
Frame (mm)	100x50 Channel, 200x12 Flat	
Axle Type	Forged Spindle CNC Machined	
No. of Disc	2	3
Type of Disc / Blade	Boron Steel / High Carbon Steel	
Disc Diameter (mm)	610 & 660, Thickness 4~6	
Disc Spacing (mm)	570 (23" Approx.) Adjustable	
Bearing Hubs	2	3
3-Point Linkage/Category	Cat-II	
Width of Cut (mm Approx)	500~550	875~925
Weight (Kg.Approx) (with 660X6mm Discs)	315	415
Tractor Power (HP)	45~55	65~75

*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification / improvement.