

- UP Model Disc Harrows are suitable for soft and medium cultivated soil conditions and for wet land preparation for sowing.
- Heavily weighted gangs provide excellent stability ideal for 30 to 65 HP tractor.
- Used in open field working for shattering of clods, preparation of soil for sowing and burial of organic substances and crop residue.
- Easy to transport in mounted condition using the tractor lift.
- High Quality bearing and hubs ensure smooth operation and put minimal load on the tractor
- High Quality seals prevent the entry of mud and water into the bearing and hubs.
- Available with the options of high carbon steel discs and high quality boron steel discs with 46-50 HRC hardness

## **Product Specifications**

Description	BEUMDH-12	BEUMDH-14	BEUMDH-16
Frame (mm)	65x8 Angle & 72x72x5 Square Tube		
Gang Bolt/ Axle Type (mm)	Round Pipe Dia. 60 with Solid Rod		
No. of Disc	12	14	16
Type of Disc / Blade	High Carbon Steel		
Disc Diameter (mm)	<b>508,</b> 560 Dia. & Thickness 3~4		
Gang Adjustable	Manual		
Disc Spacing (mm)	228 (9")		
Bearing Hubs	4 Nos.		
Pull Type	Mounted		
Width of Cut (mm)	1420	1635	1852
Weight (Kg.Approx) (with 510X6mm Discs)	360	410	465
Tractor Power (HP)	30~40	40~50	50~60

\*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification / improvement.