

- Universal Super Mould Board ploughs are equipped with Shear bolt protection to prevent any damage to the tynes or plough frame if the mould board hits a rock or hard root in the field.
- Universal Super Mould Board Ploughs are designed to work in most types of soils and can be used easily in hard soils and in cultivated/harvested areas
- Universal MB Ploughs can handle the toughest ploughing jobs with ease.
- Compatible with a variety of tractors.

- The high quality bar points can be moved in their slot for complete utilization.
- Heavy duty frame with high ground clearance makes it easy for the plough to work in fields with a lot of crop residue.
- Mould Board extension can be provided for a better control of slice when extra deep ploughing is required.
- Available in 2, 3, 4 & 5 bottom configurations.
- Equipped with special wear-resistant alloy steel blades and Boron steel bar points.

Product Specifications

Description	BEUSMBP-2	BEUSMBP-3	BEUSMBP-4	BEUSMBP-5
Frame (mm)	80x80x6 Square Tube & 100x25 Flat			100x100x6 Square Tube & 100x25 Flat
Tynes (mm)	Fabricated 25mm			
No. of Tynes & Furrow	2	3	4	5
Bar Point (mm)	Boron Steel 40 Solid Square			
Mould Board Furrow	8 mm			
3-Point Linkage / Category	Cat-I & Cat-II			
Length (mm Approx)	1320	1880	2440	3000
Width (mm Approx)	1110	1270	1430	1590
Height (mm Approx)	1240			
Width of Cut (mm Approx)	610	910	1210	1510
Weight (Kg.Approx)	250	370	505	650
Tractor Power (HP)	35~50	50~70	75~90	95~120

*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification / improvement.