

## UNIVERSAL SUPER SINGLE SPEED GEAR DRIVE Code BERTSSG



Single Speed  
Gear Box

Universal Super  
Boron Steel Blade

Helical  
Arrangement  
of Blades

Dust Cover  
Prevents  
Mud Entry



## Features & Benefits

- **Highly robust rotary tillers, suitable for most soil conditions. Appropriate for medium to hard soil conditions**
- Prepares the seed bed quickly and economically.
- Gear drive. Single speed gearbox. Compatible with 540 PTO RPM.
- Suitable for use in dry as well as wet land conditions.
- Heavy duty PTO with shear bolt for gearbox overload protection.
- Easily adjust the cutting depth by using the side skid depth adjustment.
- Comes with specially made Universal Super high quality boron steel blades that lasts much longer than other regular rotary tiller blades.
- Available in L and C type blade options.
- Innovative bearing housing and seal design prevents moisture/mud entry which results longer bearing life.
- Dust cover over both side hubs prevents mud entry.

## Product Specifications

Description	BERTSSG-125/1030	BERTSSG-150/1036	BERTSSG-175/1042	BERTSSG-200/1048
Gear Box	Single Speed			
No. of Blade	30	36	42	48
No. of Flange	6	7	8	9
Rotor Type	Seamless Pipe			
P.T.O. RPM	540			
Type of Side Drive	Gear			
Side Disc Attachment	Optional			
3-Point Linkage / Category	Cat-I & Cat-II			
Rotor Flange Diameter (mm)	230 (270 Optional)			
Gear Box Over Load Protection	Shear Bolt			
Width of Cut (cm-Approx)	125	150	175	200
Weight without PTO (Kg.Approx)	365	395	425	435
Tractor Power (HP)	35~40	40~45	45~50	50~55

\*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification / improvement.