

UNI LIGHT SINGLE SPEED GEAR DRIVE Code **BEULRTSG**



Single Speed
Gear Box

Universal Super
Boron Steel Blade

Helical
Arrangement
of Blades

Optional
PTO Guard



Features & Benefits

- **UNIVERSAL Uni-Light rotary tillers are low weight rotary tillers, highly suitable for wet land puddling for paddy cultivation.**
- Low weight rotary tiller that put minimal load on the tractor and hence ensure better fuel efficiency.
- Fast and economical solution to prepare the seed bed quickly.
- Gear drive, Single speed gearbox Compatible with 540 PTO RPM.
- Suitable for use in both dry and wet land conditions and in soft obstruction free soil conditions.
- Heavy duty PTO with shear bolt for gearbox overload protection.
- Easily adjust the cutting depth by using the side skid depth adjustment.
- Innovative bearing housing & seal design prevents the entry of mud/ moisture & gives a much longer bearing life.
- Available in L and C type blade options.
- Helical blade arrangement ensures uniform load distribution and smooth rotary tiller

Product Specifications

Description	BEULRTSG-100/7030	BEULRTSG-120/7036	BEULRTSG-140/7042	BEULRTSG-160/7048	BEULRTSG-180/7054	BEULRTSG-200/7060	BEULRTSG-220/7066	BEULRTSG-240/7072
Gear Box	Single Speed							
No. of Blade	30	36	42	48	54	60	66	72
No. of Flange	5	6	7	8	9	10	11	12
Rotor Type	Seamless Pipe							
P.T.O. RPM	540							
Type of Side Drive	Gear							
Side Disc Attachment	Optional							
3-Point Linkage / Category	Cat-I & Cat-II							
Rotor Flange Diameter (mm)	185							
Gear Box Over Load Protection	Shear Bolt / Slip Clutch PTO							
Width of Cut (cm-Approx)	100	120	140	160	180	200	220	240
Weight without PTO (Kg.Approx)	235	265	285	295	315	345	365	385
Tractor Power (HP)	20~25	25~30	30~35	35~40	40~45	45~50	50~55	55~60

*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification / improvement.