



UNIVERSAL XTRA HD

MULTI SPEED GEAR DRIVE

Code **BEXRTMSG**




Multi Speed
Gear Box

Duo Cone
Seal

Heavy Duty
Structure

Heavy Duty
Plate Lift



Features & Benefits

- **Xtra Heavy Duty Rotary tillers suitable for pulverising the thick and fibrous residue of crops such as Banana, Sugarcane, Papaya etc.**
- Extra Heavy construction for sturdy operations while crushing crops residue including the roots and the stems of crops such as Banana, Papaya, Sugarcane.
- Gear drive. Multi speed gearbox. Compatible with 540 and 1000 PTO RPM.
- Suitable for all soil types.
- Increases soil aeration and pulverisation of crop residue increases the soils fertility.
- Easily adjust the cutting depth by using the side skid depth adjustment.
- Extra heavy duty rotor and rotor flanges for toughest operating conditions
- UNIVERSAL SUPER Boron Steel Blades.
- Available in both Oil/Grease dead Hub (Optional).

Product Specifications

| Description | BEXRTMSG-150/1236 | BEXRTMSG-175/1242 | BEXRTMSG-200/1248 | BEXRTMSG-225/1254 | GEAR RATIO CHART | | | |
|--------------------------------|---------------------|-------------------|-------------------|-------------------|------------------|-----------|-----------|------------|
| Gear Box | Multi Speed | | | | | | | |
| No. of Blade | 36 | 42 | 48 | 54 | | | | |
| No. of Flange | 7 | 8 | 9 | 10 | | | | |
| Rotor Type | Seamless Pipe | | | | | | | |
| P.T.O. RPM | 540/1000 (Optional) | | | | 540 | A | B | Rotor RPM |
| Type of Side Drive | Gear | | | | | 13 | 20 | 176 |
| Side Disc Attachment | Optional | | | | | 20 | 13 | 415 |
| 3-Point Linkage / Category | Cat-I & Cat-II | | | | | 17 | 16 | 287 |
| Rotor Flange Diameter (mm) | 270 | | | | | 16 | 17 | 254 |
| Gear Box Over Load Protection | Shear Bolt | | | | | 18 | 15 | 324 |
| Width of Cut (cm-Approx) | 150 | 175 | 200 | 225 | | 15 | 18 | 225 |
| Weight without PTO (Kg.Approx) | 605 | 635 | 670 | 685 | | 14 | 19 | 199 |
| Tractor Power (HP) | 40~50 | 50~60 | 60~70 | 70~80 | 1000 | 11 | 22 | 250 |

*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification / improvement.