







Heavy Duty 3-Point Linkage

Heavy Duty Box Frame Adjustable Tynes Heavy Duty Shovels











- Universal Sub Soiler is ideal to lift and shatter the hard bed pan that builds up under soil due to compaction over time.
- Improves soil drainage. Improved soil water retention during dry season. Greatly reduced risk of water run-off during heavy rain.
- Improves soil fertility. By improving water penetration soil nutrients are
  more easily available to the plant. Moist soils heat up more easily
  during spring increasing in turn the development of soil microbes
  beneficial to plant growth.



- Optional wide range of roller/crumber available, which help in breaking lumps into smaller pieces. It also helps in depth control and steady running of the Sub Soiler.
- Adjustable depth & width.
- Optional dragging ball type attachment available with shoe assy.
- Reversible & replaceable sloped point.
- Available in 1, 2, 3 and 5 Arm sizes.

## **Product Specifications**

Description	BESS-1	BESS-2	BESS-3	BESS-5
Length (mm)	456	900	958	1140
Width (mm)	857	1232	1536	2512
Height (mm)	1050~1515			
Tyne (mm)	150x25			
No. of Arms / Tynes	1	2	3	5
3-Point Linkage	Cat-II			
Weight (Kg. Approx)	85	205	300	485
Tractor Power (HP)	40~55	60~75	80~90	100~120

<sup>\*</sup>The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification / improvement.